

# Rifrattometri

## RIFRATTOMETRO PER IL CONTROLLO DELLA CONCENTRAZIONE DELL'EMULSIONE LUBROREFRIGERANTE OPTICAL REFRACTOMETER FOR COOLANT CONCENTRATION MEASUREMENT

forniture  
per  
l'industria  
gelmini s.r.l.



Affidabile e semplice da utilizzare, basta applicare una goccia di emulsione sullo specchietto e guardare attraverso l'oculare per leggere sulla scala graduata la concentrazione.

La corretta percentuale dell'emulsione acqua-olio permette risparmio sul consumo d'olio, durata superiore dell'utensile, eliminazione della ruggine sulla macchina e su pezzi causata da emulsioni impoverite.

### **Dotazione e caratteristiche tecniche:**

Custodia antiurto e astuccio in similpelle  
Accessori per l'azzeramento  
Compensazione automatica della temperatura da 10 a 30°C  
Scala di misura: 0-32% Brix  
Precisione:  $\pm 0,2\%$   
Dimensioni: 30x40x160 mm - peso g 200



*Reliable and easy to use device, it is only necessary to drop a single drip of water-oil emulsion directly over the instrument mirror. Looking through the ocular you can directly read the concentration value.*

*Proper emulsion concentration allow costs saving on oil, longer tools life, prevent rust on machine and machined components due to low concentration emulsions.*

### **Equipment and technical data:**

Shock proof enclosure and carrying case included  
Zero adjust tools  
Auto temperature compensation from 10 to 30°C (50 to 86°F)  
Measuring scale from 0 to 32% Brix  
Accuracy:  $\pm 0,2\%$   
Dimensions: 30x40x160 mm - weight 200 g (7,06 oz)

**Forniture per l'industria gelmini s.r.l.**

**Parma** - 0521.993844 Fax 0521.291688

**Guidizzolo (MN)** - 0376.847123 Fax 0376.840319

**www.fornituregelmini.it**

Acquista ON-LINE su [www.gelmini-shop.it](http://www.gelmini-shop.it)

