


➔ Disponibili entro 3 gg (autoventilati)

AISI 304 **MOTORI ACCIAIO INOX NON VENTILATI & AUTOVENTILATI**
STAINLESS STEEL MOTORS TENV & TEFC

CARATTERISTICHE	POLI POLES	TIPO TYPE	Kw	FEATURES	
Tensione di alimentazione: 230/400V (50Hz) 265/460V (60Hz) Servizio: S1 Classe di isolamento: F Protezione IP 66 B3-B14-B5		2	SS6312	0.18	
		2	SS6322	0.25	
		2	SS7112	0.37	
		2	SS7122	0.55	
		2	SS8012	0.75	
	➔	4	SS6324	0.18	
		4	SS7114	0.25	
	➔	4	SS7124	0.37	
		4	SS8014	0.55	
	➔	4	SS8024	0.75	
		6	SS7116	0.18	
		6	SS7126	0.25	
		6	SS8016	0.37	
		6	SS8026	0.55	

AISI 304 **MOTORI ACCIAIO INOX AUTOVENTILATI**
STAINLESS STEEL TEFC MOTORS

CARATTERISTICHE	POLI POLES	TIPO TYPE	Kw	FEATURES	
Tensione di alimentazione: 230/400V (50Hz) 265/460V (60Hz) Servizio: S1 Classe di isolamento: F Protezione IP 66 B3-B14-B5		2	SS8022	1.1	
		2	SS9012	1.5	
		2	SS9022	2.2	
		2	SS10012	3	
		2	SS11212	4	
		2	SS13212	5.5	
		2	SS13222	7.5	
		4	SS9014	1.1	
	➔	4	SS9024	1.5	
		4	SS10014	2.2	
		4	SS10024	3	
		4	SS11214	4	
		4	SS13214	5.5	
		4	SS13224	7.5	
		6	SS9016	0.75	
		6	SS9026	1.1	
		6	SS10016	1.5	
		6	SS11216	2.2	
		6	SS13216	3	
		6	SS13236	4	