

Riferimento Normativa			Dimensioni	
Inglese	BS	USA	Ø Interno	Corda
2007	004	2-4	1,78	1,78
2010	005	2-5	2,57	1,78
2012	006	2-6	2,90	1,78
2015	007	2-7	3,69	1,78
2018	008	2-8	4,47	1,78
2021	009	2-9	5,28	1,78
2025	010	2-10	6,07	1,78
106	610	5-052	6,75	1,78
2031	011	2-11	7,66	1,78
108	611	5-612	8,73	1,78
2037	012	2-12	9,25	1,78
2043	013	2-13	10,82	1,78
114	806	5-613	11,11	1,78
2050	014	2-14	12,42	1,78
2056	015	2-15	14,00	1,78
2062	016	2-16	15,60	1,78
2068	017	2-17	17,16	1,78
2075	018	2-18	18,77	1,78
2081	019	2-19	20,35	1,78
2087	020	2-20	21,95	1,78
2093	021	2-21	23,52	1,78
2100	022	2-22	25,12	1,78
2106	023	2-23	26,70	1,78
2112	024	2-24	28,30	1,78
2118	025	2-25	29,87	1,78
2125	026	2-26	31,47	1,78
2131	027	2-27	33,05	1,78
2137	028	2-28	34,65	1,78
2150	029	2-29	37,82	1,78
2162	030	2-30	41,00	1,78
2175	031	2-31	44,17	1,78
2187	032	2-32	47,37	1,78
2200	033	2-33	50,52	1,78
2212	034	2-34	53,67	1,78
2225	035	2-35	56,87	1,78
2237	036	2-36	60,04	1,78
2250	037	2-37	63,22	1,78
2262	038	2-38	66,40	1,78
2275	039	2-39	69,57	1,78
2287	040	2-40	72,76	1,78
2300	041	2-41	75,94	1,78
2312	532		79,00	1,78
2325	042	2-42	82,28	1,78
2350	043	2-43	88,64	1,78
2362			91,70	1,78
2375	044	2-44	95,00	1,78
2387	538		98,05	1,78
2400	045	2-45	101,34	1,78
2412	540		104,40	1,78
2425	046	2-46	107,70	1,78
2450	047	2-47	114,00	1,78
2462	544		117,10	1,78
2475	048	2-48	120,40	1,78
2500		2-49	126,72	1,78
2525	050	2-50	133,10	1,78
2562	552		142,11	1,78
2637	558		161,16	1,78
2652	559		164,34	1,78
	105	2-105	3,63	2,62
	106	2-106	4,42	2,62
3021	107	2-107	5,23	2,62
3024	108	2-108	6,02	2,62
3030	109	2-109	7,60	2,62
109		2-110	9,13	2,62
3037	110	2-110	9,19	2,62
112	613	5-614	9,92	2,62
3043	111	2-111	10,78	2,62
115	614	5-165	11,91	2,62
3050	112	2-112	12,37	2,62
117	615	5-616	13,10	2,62
3056	113	2-113	13,95	2,62
119	616	5-243	15,08	2,62
3062	114	2-114	15,54	2,62
121	809	5-617	15,88	2,62
3068	115	2-115	17,13	2,62
123	617	5-256	17,86	2,62
3075	116	2-116	18,72	2,62
3081	117	2-117	20,29	2,62
128	812	2-117	20,64	2,62
3087	118	2-118	21,90	2,62
130	813		22,23	2,62
3093	119	2-119	23,47	2,62
132	814		23,81	2,62

Riferimento Normativa			Dimensioni	
Inglese	BS	USA	Ø Interno	Corda
3100	120	2-120	25,07	2,62
3106	121	2-121	26,65	2,62
3112	122	2-122	28,25	2,62
3118	123	2-123	29,83	2,62
3125	124	2-124	31,42	2,62
3131	125	2-125	33,00	2,62
3137	126	2-126	34,60	2,62
3143	127	2-127	36,17	2,62
3150	128	2-128	37,77	2,62
3156	129	2-129	39,35	2,62
3162	130	2-130	40,95	2,62
3168	131	2-131	42,52	2,62
3175	132	2-132	44,12	2,62
3181	133	2-133	45,70	2,62
3187	134	2-134	47,30	2,62
3193	135	2-135	48,90	2,62
3200	136	2-136	50,47	2,62
3206	137	2-137	52,07	2,62
3212	138	2-138	53,65	2,62
3218	139	2-139	55,25	2,62
3225	140	2-140	56,82	2,62
3231	141	2-141	58,42	2,62
3237	142	2-142	60,00	2,62
3243	143	2-143	61,60	2,62
3250	144	2-144	63,17	2,62
3256	145	2-145	64,77	2,62
3262	146	2-146	66,35	2,62
3268	147	2-147	67,95	2,62
3275	148	2-148	69,52	2,62
3281	149	2-149	71,12	2,62
3287	150	2-150	72,70	2,62
3300	151	2-151	75,88	2,62
3325	152	2-152	82,22	2,62
3350	153	2-153	88,58	2,62
3375	154	2-154	94,93	2,62
3400	155	2-155	101,28	2,62
3425	156	2-156	107,63	2,62
3450	157	2-157	113,98	2,62
3475	158	2-158	120,33	2,62
3500	159	2-159	126,67	2,62
3525	160	2-160	133,00	2,62
3550	161	2-161	139,38	2,62
3575	162	2-162	145,73	2,62
3600	163	2-163	152,07	2,62
3625	164	2-164	158,43	2,62
3650	165	2-165	164,78	2,62
3675	166	2-166	171,13	2,62
3700	167	2-167	177,48	2,62
3725	168	2-168	183,83	2,62
3750	169	2-169	190,18	2,62
3775	170	2-170	196,53	2,62
3800	171	2-171	202,88	2,62
3825	172	2-172	209,23	2,62
3850	173	2-173	215,57	2,62
3875	174	2-174	221,93	2,62
3900	175	2-175	228,28	2,62
3925	176	2-176	234,63	2,62
3950	177	2-177	240,98	2,62
3975		2-178	247,32	2,62
4028	203	2-203	7,52	3,53
4036	204	2-204	9,13	3,53
4042	205	2-205	10,69	3,53
4050		2-206	12,29	3,53
4055		2-207	13,87	3,53
4061	208	2-208	15,47	3,53
4067		2-209	17,04	3,53
4075	210	2-210	18,64	3,53
4081	211	2-211	20,22	3,53
4087	212	2-212	21,82	3,53
4093	213	2-213	23,40	3,53
4100	214	2-214	25,00	3,53
134	618	5-618	25,80	3,53
4106	215	2-215	26,57	3,53
4112	216	2-216	28,17	3,53
4118	217	2-217	29,75	3,53
4125	218	2-218	31,34	3,53
4131	219	2-219	32,93	3,53
4137	220	2-220	34,52	3,53
4143	221	2-221	36,10	3,53
4150	222	2-222	37,70	3,53
144	824	5-321	39,70	3,53
4162	223	2-223	40,87	3,53
146	825	6-525	41,28	3,53

Riferimento Normativa			Dimensioni	
Inglese	BS	USA	Ø Interno	Corda
147	826	5-332	42,86	3,53
4175	224	2-224	44,05	3,53
149	827		44,45	3,53
150	828	6-159	46,04	3,53
4187	225	2-225	47,23	3,53
152	829		47,62	3,53
153	830	5-701	49,20	3,53
4200	226	2-226	50,40	3,53
155	831		50,80	3,53
156	832	5-037	52,40	3,53
4212	227	2-227	53,57	3,53
158	833		53,97	3,53
159	834		55,56	3,53
4225	228	2-228	56,75	3,53
161	835		57,15	3,53
162	836	5-702	58,74	3,53
4237	229	2-229	59,92	3,53
164	837		60,32	3,53
165	838		61,90	3,53
4250	230	2-230	63,10	3,53
167	839		63,50	3,53
168	840	5-703	65,10	3,53
4262	231	2-231	66,27	3,53
170	841		66,67	3,53
171	842		68,26	3,53
4275	232	2-232	69,44	3,53
173	843		69,85	3,53
174	844	5-704	71,44	3,53
4287	233	2-233	72,76	3,53
176	845		73,02	3,53
177	846	5-705	74,60	3,53
4300	234	2-234	75,80	3,53
4312	235	2-235	78,97	3,53
4325	236	2-236	82,14	3,53
4337	237	2-237	85,32	3,53
4350	238	2-238	88,50	3,53
4362	239	2-239	91,67	3,53
4375	240	2-240	94,84	3,53
4387	241	2-241	98,02	3,53
4400	242	2-242	101,20	3,53
4412	243	2-243	104,37	3,53
4425	244	2-244	107,54	3,53
4437	245	2-245	110,72	3,53
4450	246	2-246	113,90	3,53
4462	247	2-247	117,07	3,53
4475	248	2-248	120,24	3,53
4487	249	2-249	123,42	3,53
4500	250	2-250	126,60	3,53
4512	251	2-251	129,77	3,53
4525	252	2-252	132,94	3,53
4537	253	2-253	136,12	3,53
4550	254	2-254	139,30	3,53
4562	255	2-255	142,47	3,53
4575	256	2-256	145,65	3,53
4587	257	2-257	148,82	3,53
4600	258	2-258	152,00	3,53
4625	259	2-259	158,35	3,53
4650	260	2-260	164,70	3,53
4675	261	2-261	171,05	3,53
4700	262	2-262	177,40	3,53
4725	263	2-263	183,75	3,53
4750	264	2-264	190,10	3,53
4775	265	2-265	196,45	3,53
4800	266	2-266	202,80	3,53
4825	267	2-267	209,15	3,53
4850	268	2-268	215,50	3,53
4875	269	2-269	221,85	3,53
4900	270	2-270	228,20	3,53
4925	271	2-271	234,55	3,53
4950	272	2-272	240,90	3,53
4975	273	2-273	247,25	3,53
41000	274	2-274	253,60	3,53
41050	275	2-275	266,30	3,53
41100	276	2-276	279,00	3,53
41150	277	2-277	291,70	3,53
41200	278	2-278	304,40	3,53
41300	279	2-279	329,80	3,53
41400	280	2-280	355,20	3,53
41500	281	2-281	380,60	3,53
41600	282	2-282	405,26	3,53
41700	283	2-283	430,66	3,53
41800		2-284	456,06	3,53
		2-315	19,99	5,34

Riferimento Normativa			Dimensioni	
Inglese	BS	USA	Ø Interno	Corda
	318	2-318	24,77	5,34
	321	2-321	29,51	5,34
	324	2-324	34,29	5,34
6150	325	2-325	37,47	5,34
6162	326	2-326	40,65	5,34
6175	327	2-327	43,82	5,34
6187	328	2-328	47,00	5,34
6200	329	2-329	50,16	5,34
6212	330	2-330	53,34	5,34
6225	331	2-331	56,52	5,34
6237	332	2-332	59,70	5,34
6250	333	2-333	62,87	5,34
6262	334	2-334	66,04	5,34
6275	335	2-335	69,22	5,34
6287	336	2-336	72,40	5,34
178	619		74,63	5,34
6300	337	2-337	75,57	5,34
6312	338	2-338	78,74	5,34
181	620	9-504	79,77	5,34
6325	339	2-339	81,92	5,34
6337	340	2-340	85,10	5,34
6350	341	2-341	88,27	5,34
185	621		89,69	5,34
6362	342	2-342	91,44	5,34
6375	343	2-343	94,62	5,34
6387	344	2-344	97,80	5,34
189	622	9-591	100,00	5,34
6400	345	2-345	100,97	5,34
6412	346	2-346	104,14	5,34
6425	347	2-347	107,32	5,34
193	623		109,54	5,34
6437	348	2-348	110,50	5,34
6450	349	2-349	113,67	5,34
199	860		117,48	5,34
201	861		120,65	5,34
203	862	9-664	123,83	5,34
206	863		127,00	5,34
208	864		130,18	5,34
210	865		133,35	5,34
213	866		136,53	5,34
215	867		139,70	5,34
217	868		142,88	5,34
219	869		146,05	5,34
221	870		149,23	5,34
6600	361	2-361	151,77	5,34
6625	362	2-362	158,12	5,34
6645	363	2-363	164,47	5,34
6670	364	2-364	170,82	5,34
6700	365	2-365	177,17	5,34
6720	366	2-366	183,52	5,34
6745	367	2-367	189,87	5,34
6775	368	2-368	196,22	5,34
6795	369	2-369	202,57	5,34
6820	370	2-370	208,92	5,34
6850	371	2-371	215,27	5,34
6870	372	2-372	221,62	5,34
6895	373	2-373	227,97	5,34
6920	374	2-374	234,32	5,34
6945	375	2-375	240,67	5,34
6975	376	2-376	247,02	5,34
6995	377	2-377	253,37	5,34
61050	378	2-378	266,07	5,34
61100	379	2-379	278,77	5,34
61150	380	2-380	291,47	5,34
61200	381	2-381	304,17	5,34
61300	382	2-382	329,67	5,34
61400	383	2-383	354,97	5,34
61500	384	2-384	380,37	5,34
61600	385	2-385	405,26	5,34
61700	386	2-386	430,66	5,34
61800	387	2-387	456,06	5,34
61900	388	2-388	481,41	5,34
62000	389	2-389	506,81	5,34
62100	390	2-390	532,20	5,34
62200	391	2-391	557,61	5,34
62300	392	2-392	582,62	5,34
62400	393	2-393	608,08	5,34
62500	394	2-394	633,48	5,34
62600	395	2-395	658,88	5,34
8450	425	2-425	113,67	6,99
197	624		114,70	6,99
8462	426	2-426	116,84	6,99
8475	427	2-427	120,02	6,99

Riferimento Normativa			Dimensioni	
Inglese	BS	USA	Ø Interno	Corda
8487	428	2-428	123,20	6,99
204	625		124,60	6,99
8500	429	2-429	126,37	6,99
8512	430	2-430	129,54	6,99
8525	431	2-431	132,72	6,99
211	626		134,50	6,99
8537	432	2-432	135,90	6,99
8550	433	2-433	139,07	6,99
8562	434	2-434	142,24	6,99
8575	435	2-435	145,42	6,99
8587	436	2-436	148,60	6,99
8600	437	2-437	151,77	6,99
223	872		155,60	6,99
8625	438	2-438	158,12	6,99
225	627		159,50	6,99
226	874		161,90	6,99
8650	439	2-439	164,47	6,99
228	628		166,70	6,99
229	876		168,30	6,99
8675	440	2-440	170,82	6,99
231	878		174,60	6,99
8700	441	2-441	177,17	6,99
233	880		181,00	6,99
8725	442	2-442	183,52	6,99
235	882		187,30	6,99
8750	443	2-443	189,87	6,99
237	884		193,70	6,99
8775	444	2-444	196,22	6,99
239	886		200,00	6,99
8800	445	2-445	202,57	6,99
8825	674		208,92	6,99
8850	446	2-446	215,27	6,99
8875	676		221,62	6,99
8900	447	2-447	227,97	6,99
8925	678		234,32	6,99
8950	448	2-448	240,67	6,99
8975	680		247,00	6,99
81000	449	2-449	253,57	6,99
81025	682		259,70	6,99
81050	450	2-450	266,07	6,99
81075	684		272,40	6,99
81100	451	2-451	278,77	6,99
81125	686		285,10	6,99
81150	452	2-452	291,47	6,99
81175	688		297,80	6,99
81200	453	2-453	304,17	6,99
81250	454	2-454	316,87	6,99
81300	455	2-455	329,57	6,99
81350	456	2-456	342,27	6,99
81400	457	2-457	354,97	6,99
81450	458	2-458	367,67	6,99
81500	459	2-459	380,37	6,99
81550	460	2-460	393,07	6,99
81600	461	2-461	405,26	6,99
81650	462	2-462	417,96	6,99
81700	463	2-463	430,66	6,99
81750	464	2-464	443,36	6,99
81800	465	2-465	456,06	6,99
81850	466	2-466	468,76	6,99
81900	467	2-467	481,46	6,99
81950	468	2-468	494,16	6,99
82000	469	2-469	506,86	6,99
82100	470	2-470	532,26	6,99
82200	471	2-471	557,66	6,99
82300		2-472	582,68	6,99
82400		2-473	608,80	6,99
82500		2-474	633,48	6,99
82600		2-475	658,88	6,99